




## CLASSTIG 160E



**Decoration Industrial**  **DC 1**  
Phase

### Processes

- TIG(GTAW)
- STICK(SMAW)

### Optional Accessories

- Earth cable and clamp
- Welding cable and holder
- Suitcase
- Lift Tig Torch
- Regulator



- ☑ HF Mode-High Frequency TIG Mode
- ☑ Selectable Post Flow time
- ☑ High duty cycle for industrial applications
- ☑ Compact and portable with light weight
- ☑ 2T/4T mode for earier working Except TIG180E
- ☑ Selectable down slope time (Except TIG 180E)
- ☑ Generator friendly allows to work with diesel generators and to avoid failures due to its voltage spikes
- ☑ Protections including over-heat ,over-voltage,low-voltage and over-current

MODEL	CLASSTIG 160 E	
Power Supply Voltage (V)	160-275	
Fre.(HZ)	50/60	
Function	TIG	MMA
Rated Input Power (KW)	3.5	4.9
Rated Input Current (A)	27	37
Duty Cycle (40°C 10min)	40% 180A	40% 180A
	40% 180A	40% 180A
	40% 180A	40% 180A
No Load Voltage (V)	74	
Welding Current Range (A)	10-160	10-145
Net Weight (KG)/(LB)	3.5 KG/7.7 LB	
Dimensions (MM)/(Inch)	220*120*170/8.7*4.7*6.7	
Welding Voltage Range (V)	0-10	
Power Factor	0.75	

www.crepow.com  
 Choice Prove Tig Series

www.crepow.com

CE  RoHS 

  
**CREPOW®**  
 Welding & Cutting Technology